

English

Operator's Guide

LOGIN, LOGOUT

Login

Confirm that the terminal unit is idle then do the following:

1. Confirm that [SYNC (NCS)] appears at the bottom of the screen.
2. Press the **F7** key to display the [Options] menu.

| Options | |
|--------------------|--|
| 1. Position | |
| 2. Login | |
| 3. Logout | |
| 4. Abort | |
| 5. Select NCS | |
| 6. Ocean Region | |
| 7. LES Information | |
| 8. Test | |
| 9. Maintenance | |

3. Press the **2** key to display the [Login] screen.

| Login | |
|-----------------|--|
| Start | |
| ----- | |
| Yes No | |

4. [Yes] is selected in the [Start] window; press the **Enter** key to start the login process.

When login is completed, the message "Successful Login" appears. Press the **Esc** key to go to the standby display.

Logout

1. Press the **F7** and **3** keys to display the [Logout] screen.
2. [Yes] is selected in the [Start] window; press the **Enter** key to start the logout process.

When logout is completed, the message "Successful Logout." appears and the [Current State] indication changes from [LOGOUT] to [IDLE]. Then, turn off the FELCOM.

HOW TO SEND A MESSAGE TO A STATION SAVED TO THE STATION LIST

1. Prepare message on the screen.
For e-mail, set [Text Mode] in the [Editor Setup] menu to [Ascii].
2. Press the **F3** key to display the [Transmit] menu.

| Transmit | |
|----------------------------|--|
| 1. Transmit Message | |
| 2. Cancel | |
| 3. Request Delivery Status | |

3. Press the **1** key to display the [Transmit Message] menu.

| Transmit Message | | | |
|--------------------|------------|------|----|
| Priority | Normal | Size | 24 |
| Message File | | | |
| Station Name | | | |
| Destination Type | TELEX/MES | | |
| Prefix Code | | | |
| Country/Ocean Code | 82 | | |
| Destination | 65-2111 | | |
| Modem Type | | | |
| Address | | | |
| Subject | | | |
| Attach File | | | |
| LES ID | 303 (KDDI) | | |
| Option | ON | | |
| Confirmation | 00:00 | | |
| Send Delay | Immediate | | |
| Delivery Delay | IA5 | | |
| Code | | | |
| [TRANSMIT] | | | |

4. Select [Station Name] then press the **Enter** key to open the Station List.

| Station List | | | | |
|---|---------------|---------------|-----------|----------------------|
| Group | Station Name | Type | Code | ID / Address |
| 01 | FURUNO | TELEX/ | 81 | 321 |
| 02 | FRNINMBTSTS | TELEX/ | 583 | 343199999 |
| 03 | Seagull | E-Mail | | Seagull@furuno.co.jp |
| 04 | whale | E-Mail | | whale@furuno.co.jp |
| 05 | | | | |
| 06 | | | | |
| 07 | | | | |
| 08 | | | | |
| ----- | | | | |
| ↑ ↓: Select SPACE: Select Stations B.SPACE: Cancel Mark INS: Edit Sort (Ctrl+G: Group, Ctrl+N: Station Name, Ctrl+T: Type) | | | | |

5. Choose a station then press the **Enter** key. To select multiple stations (simultaneous transmission), select a station and then press the Spacebar.
6. For e-mail do the following. For other types, go to step 7.
 - 1) Select [Subject] then press the **Enter** key.
 - 2) Type subject then press the **Enter** key.
 - 3) To attach a file, select [Attach File] then press the **Enter** key.
 - 4) Press the **Enter** key to open the file list.
 - 5) Select a file then press the **Enter** key.
 - 6) Press the **Esc** key to close the window. Go to step 7.

7. Select [LES ID] then press the **Enter** key to open the LES setting window.

| Name | LES ID | Remarks |
|----------------|--------|-------------|
| Vizada 201 | 201 | USA |
| Stratos Global | 202 | CANADA |
| KDDI | 203 | JAPAN |
| Vizada (NOR) | 204 | NORWAY |
| Korea Telecom | 208 | SOUTH KOREA |

8. Select an LES then press the **Enter** key.
9. Select [Confirmation] then press the **Enter** key.
10. To request notification of delivery from the LES, select [ON]. If not necessary select [OFF]. Press the **Enter** key.
11. Select [Send Delay] then press the **Enter** key. To send a message after a certain delay, enter a time up to 99 hours 59 minutes. Press the **Enter** key.
12. Select [Delivery Delay] then press the **Enter** key. Select [Immediate] or [Deferred] then press the **Enter** key.
13. Select [Code] then press the **Enter** key.
14. Select [IA5] then press the **Enter** key.
15. Put the cursor on [TRANSMIT] then press the **Enter** key to show the [Start] window.
16. Press the **Enter** key to send the message to the message queue.
17. Long-press the **Esc** key to return to the standby display.

If the message was sent successfully, "Successful Sending message" appears and the TX message is printed (if [Confirmation] is OFF).

How to cancel transmission on a message awaiting transmission

Press the **F3** and **2** keys to show the [Cancel] screen.

| Cancel | | | | | | |
|--------|--------------|-------------|------------|----------|---------|--------|
| No. | Message File | Destination | LES | Priority | Send | Status |
| 01 | S11111.001 | INET | Vizada 101 | Normal | Sending | |

Select the message to cancel then press the **Enter** key. Press the **Enter** key again to cancel the message.

HOW TO SEND A DATA REPORT AT REGULAR INTERVALS

1. Press the **F5** and **1** keys to show the [Data Report] menu.
2. Press the appropriate numeric key to select a data report.

| Data Report | |
|-------------------------|---------------------------|
| Data Report Programming | |
| Status | OFF |
| Report Length | Position and Course/Speed |
| Destination | |
| DNID | |
| LES ID | |
| Member No. | |
| Activation | Regular Interval |
| Interval Time | 00:10 |
| Report Times | 1 (---: No Limit) |
| Start Time1 | --:-- |
| Start Time2 | --:-- |
| Start Time3 | --:-- |
| Start Time4 | --:-- |

3. Press the **Enter** key to open the status options window.
4. Select appropriate option then press the **Enter** key.
 - OFF**: Data report off
 - ON**: Enhanced Data Report (Data report w/confirmation)
 - ON**: Usual Data Report (Standard data report)
5. Select [Report Length] then press the **Enter** key.
6. Select appropriate option then press the **Enter** key.
 - Position only**: Own position
 - Position and Course/Speed**: Position, course and speed
 - Position and Course/Speed with SEA INF**: Position, course, speed, water temperature, tide, and depth
7. Select [DNID] then press the **Enter** key.
8. Select DNID desired then press the **Enter** key.
9. Select [LES ID] then press the **Enter** key.
10. Select LES ID desired then press the **Enter** key.
11. Select [Member No.] then press the **Enter** key.
12. Select Member No. desired then press the **Enter** key.
13. Select [Activation] then press the **Enter** key.
14. Select [Regular Interval] then press the **Enter** key.
15. Select [Interval Time] then press the **Enter** key.
16. Key in interval time then press the **Enter** key.
17. Select [Report Times] then press the **Enter** key.
18. Key in the report times, or press the **BackSpace** key to display "---" to select [No Limit] to transmit data until the Status setting is turned OFF. Press the **Enter** key.
19. Press the **Enter** key to close the window.

